



Hand Sanding



## Cloth Sheets

## Aluminum Oxide (DA-F)

- Aluminum oxide grain on a flexible cloth backing
- Open coat structure prevents loading
- Water resistant
- Long life combined with excellent stock removal
- **Excellent for woodworking applications**

**WOOD** Wood, plastic, fiberglass

**METAL** Ferrous and/or non-ferrous materials (iron, steel, copper, etc.)

- Available in F-weight - high flexibility

	Size	Grit	Part No.	Std Pkg.
Aluminum Oxide	9 x 11 DA-F	36	84907	25
		40	84908	25
		50	84909	25
		60	84910	25
		80	84911	25
		100	84912	50
		120	84913	50
		150	84914	50
		180	84915	50
		220	84916	50
		240	84917	50
		320	84918	50



## Paper Sheets

## Aluminum Oxide (AW-C & AW-D)

- Extremely long lasting
- Open coat structure prevents loading
- Use wet or dry

**WOOD** Wood, sealers, fillers

**METAL** Ferrous and/or non-ferrous metals

- Available in grits up to 1200 for ultra fine finishing
- Available in weights: "C"-medium weight, medium flexibility  
"D"-heavy weight, low flexibility

## Garnet

- Natural garnet grain
- Open coat structure prevents loading
- Use dry only

**WOOD** Soft woods

- Available in weights: "A"-light weight, high flexibility  
"C"-medium weight, medium flexibility  
"D"-heavy weight, low flexibility

	Size	Grit Wgt.	Part No.	Std Pkg.
Aluminum Oxide	9 x 11 AW-D	40D	84211	100
		50D	84212	100
		60D	84213	100
		80D	84214	100
		100D	84215	100
		120D	84216	100
		Garnet	9 x 11 AW-C	150C
180C	84201			100
220C	84202			100
240C	84203			100
320C	84204			100
400C	84205			100
500C	84206			100
600C	84207			100
800C	84208			100
1200C	84209			100
Garnet	9 x 11			50D
		60D	84102	50
		80D	84103	50
		100C	84104	100
		120C	84105	100
		180A	84107	100
220A	84108	100		



- Resin over resin construction for a strong bond resistant to heat and moisture
- Cloth backing for durability and flexibility
- Box label UPC bar coded for easy identification and inventory maintenance
- Our highest quality industrial paper for extra durability on all applications
- Broad assortment of grit sizes for a wide range of sanding and finishing applications
- Strong resin over resin bond construction is resistant to heat and moisture



## Premium Stearate Aluminum Oxide (4S)

- Premium aluminum oxide
- **Stearate coating and open coat structure lubricates and prevents loading**
- Long lasting performance and fast removal rates for fine finishing of automotive body works and wood finishing
- Use dry only
- Available in C-weight - medium weight, low flexibility

**WOOD** Body filler, paint, fiberglass, wood and fiberglass

**METAL** Ferrous and non-ferrous metals

## Stearate Aluminum Oxide (3S)

- Extremely long lasting
- **Open coat structure prevents loading**
- Use dry only

**WOOD** Sealers, body filler, paint, fiberglass, wood

**METAL** Aluminum

- Available in grits up to 500 for fine finishing
- Available in C-weight - medium weight, medium flexibility



COATED ABRASIVES

SHEETS

Stearate Aluminum Oxide	Size	Grit Wgt.	Part No.		Std Pkg.
			3S	4S	
9 x 11	80C	84230	84283	100	
	100C	84231	84284	100	
	120C	84232	84285	100	
	150C	84233	84286	100	
	180C	84234	84287	100	
	220C	84235	84288	100	
	240C	84236	84289	100	
	320C	84237	84290	100	
	400C	84238	84291	100	
	500C	84239	84292	100	
	600C	-	84293	100	

## Waterproof Silicon Carbide (CW-C)

- Extremely long lasting
- **Closed coat structure for more material removal**
- Use wet or dry

**WOOD** Varnish, plastic, fiberglass, clear coat, primer

**CONCRETE** Marble, ceramics

**METAL** Ferrous and/or non-ferrous metals

- Available in grits up to 2000 for ultra fine finishing
- Available in C-weight - medium weight, medium flexibility

### Waterproof Silicon Carbide

Size	Grit Wgt.	Part No.	Std Pkg.
9 x 11 CW-C	80C	84249	100
	100C	84250	100
	120C	84251	100
	150C	84252	100
	180C	84253	100
	220C	84254	100
	240C	84255	100
	320C	84256	100
	400C	84257	100
	500C	84258	100
	600C	84259	100
	800C	84260	100
	1200C	84261	100
5-1/2 x 9 CW-C	1000C	84270	50
	1200C	84271	50
	1500C	84274	50
	2000C	84277	50