



The Original **Self-Drilling Drywall Anchor**

DESCRIPTION/SUGGESTED SPECIFICATIONS

SPECIFIED FOR ANCHORAGE INTO GYPSUM WALLBOARD



The E-Z Ancor is a one-piece self-drilling anchor designed for optimal holding performance in gypsum wallboard. Available in zinc or high strength engineered plastic (non-conductive). Ideal anchor for 3/8", 1/2" and 5/8" gypsum wallboard.

ADVANTAGES

- Fast—no pre-drilling
- Easy—just use #2 phillips bit
- Clean and neat-tri-cut point drills a small hole and seats flush

PPLICATIONS

Removable—easily backed out of wallboard

Corrosion resistance

Breakaway point for easy usage when cavity is shallow

Shelving

Closet organizers

Curtain rods

Signage






EZ100 Zinc **EZPPL100 Plastic**

EZT50 Toggle



INSTALLATION STEPS



recess of E-Z Ancor.

screwdriver (#2 phillips bit) into

ELECTION CHART

2. Press into

Gypsum wallboard while turning the anchor clockwise until seated flush.

Electrical fixtures

Bathroom accessories

HVAC fixtures

3. Place fixture in position over installed E-Z Ancor. Insert screw (#8A or AB screws are recommended). Tighten fixture into place.

E-Z Ancor Kits

Starter Kit Part Number: EZ25 **Kit Contains:** 25 Zinc Anchors 25 Screws



Starter Kit Part Number: EZP25 **Kit Contains:** 25 Plastic Anchors 25 Screws



冬 RED HEAD'

E-ZANCOR * Not for overhead								
PART NUMBER	DESCRIPTION	QTY/WT PER BOX Ibs.	QTY/WT PER MASTER CARTON Ibs.					
EZ100	Zinc E-Z Ancor	100/ 1.6	1000/17.0					
EZPPL100	Plastic E-Z Ancor	100/ 0.1	1000/ 4.2					
EZP25	25 Plastic Anchors/25 Screws (#8 - 1-1/4" sheet metal screws)	1/ 0.9	10/ 3.0					
EZ25	25 Zinc Anchors/25 Screws (#8 – 1-1/4" sheet metal screw)	1/ 0.9	10/ 10					
EZT50	EZ TOGGLE/50 #2 Phillips screws	50/ 2.4	250/ 12					

PERFORMANCE TABLE

	E-Z /	Ancor				
MAXIMUM FIXTURE	ULTIMATE PULLOUT LBS. GYPSUM BOARD THICKNESS		ULTIMATE SHEAR LBS. GYPSUM BOARD THICKNESS			
THICKNESS	3/8″	1/2″	5/8″	3/8″	1/2″	5/8″
3/4″	40	50	75	135	150	200

Divide by 4 for allowable load values.

