

BENCH WHEELS



Bench Grinder

A

- Aluminum oxide grain
- General purpose
- For sharpening tools and light stock removal

METAL Ferrous metals
(carbon steel, steel, iron, forgings, etc.)

GC

- Green silicon carbide grain
- Extremely sharp grain for faster, burr-free cutting
- Use on carbide tipped tools, cast iron

METAL Ferrous and/or non-ferrous metals



Reduction bushings enclosed with each wheel

Wheel Size	Bushings
6"	3/4, 5/8, 1/2
7"	3/4, 5/8, 1/2
8"	3/4, 5/8
10"	1, 3/4
12"	1-1/4, 1
14"	1-1/4, 1

Aluminum Oxide

Size			Max RPM	Grades Available					Lbs Per Box
A Dia.	B Width	C Bore		Part Numbers					
				A24	A36	A46	A60	A80	
6	1/2	1	4,138	-	28003	-	28004	28005	1-1/2
6	3/4	1	4,138	-	28000	-	28001	28002	2
6	1	1	4,138	-	28006	-	28007	28008	2-1/2
7	3/4	1	3,600	-	28010	-	28011	28012	2-1/2
7	1	1	3,600	-	28013	-	28014	28015	3-1/2
8	3/4	1	3,600	-	28020	-	28021	28022	3-1/2
8	1	1	3,600	-	28023	-	28024	28025	4-1/2
10	1	1-1/4	2,483	-	28040	28043	28041	28042	7
10	1-1/2	1-1/4	2,483	-	28050	28053	28051	28052	10
12	2	1-1/2	2,069	28060	28063	28061	28062	-	19-1/2
14	2	1-1/2	1,773	28070	28073	28071	28072	-	28

Green Silicon Carbide

Size			Max RPM	Grades Available			Lbs Per Box
A Dia.	B Width	C Bore		Part Numbers			
				GC60	GC80	GC120	
6	3/4	1	4,138	28100	28101	28102	1-1/2
6	1	1	4,138	28103	28104	28105	2
7	1	1	3,600	28113	28114	28115	2-1/2
8	1	1	3,600	28123	28124	28125	3-1/2
10	1	1-1/4	2,483	28140	28141	28142	6-1/2
10	1-1/2	1-1/4	2,483	28150	28151	28152	10
12	2	1-1/2	2,069	28160	28161	28162	19-1/2
14	2	1-1/2	1,773	28170	28171	28172	28



- Vitrified bond for long life
- Available in two formulations for a wide range of applications
- Individually packaged for safety and convenience

VITRIFIED

VITRIFIED